

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number
WO 2005/035421 A1

(51) International Patent Classification⁷: **B66B 13/12**,
13/16

(21) International Application Number:
PCT/US2003/029827

(22) International Filing Date:
18 September 2003 (18.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MILLER, Robin Mihekun** [US/US]; 125 Burbank Road, Ellington, CT 06029 (US). **GALANTE, Timothy P.** [US/US]; 5 Cherryfield Drive, West Hartford, CT 06107 (US).

(74) Agent: **LABA, Kerrie A.**; Carlson, Gaskey & Olds, 400 West Maple Road, Suite 350, Birmingham, MI 48009 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

[Continued on next page]

(54) Title: **ELEVATOR ASSEMBLY WITH EXTENDABLE SILL**



(57) **Abstract:** An elevator (20) includes a sill (38) that extends out from underneath an elevator car (30) to bridge an operating gap (26) between the car (30) and a landing (24). When an elevator door (34) is aligned with a landing door (36), the sill (38) extends outwardly from the car (30) until the sill (38) makes contact with a landing structure (40). A locking mechanism (52) securely locks the sill (38) to the landing structure (40). In one example, once proper sill alignment and locking engagement occurs, a door moving mechanism (50) is released and the elevator (34) and landing (36) doors open.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.